

INTERNAL COMBUSTION COUNTERBALANCED
FORKLIFT TRUCK

4-5 ton

WIDE VIEW MAST

Mast model	Max. Lifting height	Load capacity(Load center 500mm)(kg)			Height mast retracted (C)(mm)	Tilting angles Forward /backward	Service Weight (kg)					
		CPC(D)40	CPC(D)45	CPC(D)50			CPCD40	CPCD45	CPCD50	CPC40	CPC45	CPC50
M260	2600	4000	4500	5000	2075	6° / 12°	6450	6750	7050	6150	6450	6750
M270	2700	4000	4500	5000	2125	6° / 12°	6475	6775	7075	6175	6475	6775
M300	3000	4000	4500	5000	2275	6° / 12°	6500	6800	7100	6200	6500	6800
M330	3300	4000	4500	5000	2425	6° / 12°	6515	6815	7115	6215	6515	6815
M350	3500	4000	4500	5000	2525	6° / 12°	6525	6825	7125	6225	6525	6825
M370	3700	4000	4500	5000	2625	6° / 12°	6535	6835	7135	6235	6535	6835
M375	3750	4000	4500	5000	2650	6° / 12°	6540	6840	7140	6240	6540	6840
M400	4000	4000	4500	5000	2825	6° / 6°	6550	6850	7150	6250	6550	6850
M425	4250	3800 *4000	4300 *4500	4700 *5000	2950	6° / 6°	6560	6860	7160	6260	6560	6860
M450	4500	3700 *4000	4200 *4500	4500 *5000	3075	6° / 6°	6575	6875	7175	6275	6575	6875
M475	4750	3500 *3700	4000 *4200	4250 *4600	3200	6° / 6°	6590	6890	7190	6290	6590	6890
M500	5000	3200 *3400	3600 *4000	4000 *4200	3325	6° / 6°	6600	6900	7200	6300	6600	6900
M550	5500	2900 *3100	3200 *3600	3600 *3800	3575	3° / 6°	6630	6930	7230	6330	6630	6930
M600	6000	2600 *2900	3000 *3200	3300 *3600	3825	3° / 6°	6650	6950	7250	6350	6650	6950

Note: * Refers to the rated capacity with front dual tyre.

WIDE VIEW FULL FREE 2-STAGE MAST

Mast model	Max. Lifting height	Load capacity(Load center 500mm)(kg)			Height mast retracted (C)(mm)	Free lift (with backrest) (mm)	Full free lift (mm)	Tilting angles Forward /backward	Service Weight (kg)					
		CPC(D)40	CPC(D)45	CPC(D)50					CPCD40	CPCD45	CPCD50	CPC40	CPC45	CPC50
ZM261	2610	4000	4500	5000	2180	960	1380	6° / 12°	6475	6775	7075	6175	6475	6775
ZM271	2710	4000	4500	5000	2230	1010	1430	6° / 12°	6500	6800	7100	6200	6500	6800
ZM300	3000	4000	4500	5000	2375	1155	1575	6° / 12°	6550	6850	7150	6250	6550	6850
ZM330	3300	4000	4500	5000	2525	1305	1725	6° / 12°	6565	6865	7165	6265	6565	6865
ZM350	3500	4000	4500	5000	2625	1405	1825	6° / 12°	6575	6875	7175	6275	6575	6875
ZM375	3750	4000	4500	5000	2750	1530	1950	6° / 12°	6590	6890	7190	6290	6590	6890
ZM400	4000	4000	4500	5000	2875	1655	2075	6° / 6°	6605	6905	7205	6305	6605	6905
ZM450	4500	3700 *4000	4200 *4500	4500 *5000	3125	1905	2326	6° / 6°	6630	6930	7230	6330	6630	6930
ZM500	5000	3200 *3400	3600 *4000	4000 *4200	3375	2155	2576	6° / 6°	6665	6965	7265	6365	6665	6965
ZM550	5500	2900 *3100	3200 *3600	3600 *3800	3625	2405	2826	3° / 6°	6690	6990	7290	6390	6690	6990
ZM600	6000	2600 *2900	3000 *3200	3300 *3600	3875	2655	3076	3° / 6°	6715	7015	7315	6415	6715	7015

Note: (1)Free lift (without backrest) : +380mm;
(2)* Refers to the rated capacity with front dual tyre.

WIDE VIEW FULL FREE 3-STAGE MAST

Mast model	Max. Lifting height	Load capacity(Load center 500mm)(kg)			Height mast retracted (C)(mm)	Free lift (with backrest) (mm)	Full free lift (mm)	Tilting angles Forward /backward	Service Weight (kg)					
		CPC(D)40	CPC(D)45	CPC(D)50					CPCD40	CPCD45	CPCD50	CPC40	CPC45	CPC50
ZSM392	3920	3840 *4000	4350 *4500	4800 *5000	2235	1012	1430	6° / 6°	6700	7000	7300	6400	6700	7000
ZSM435	4350	3500 *3800	4100 *4300	4400 *4800	2380	1157	1575	6° / 6°	6740	7040	7340	6440	6740	7040
ZSM450	4500	3350 *3500	4000 *4200	4200 *4700	2430	1208	1625	6° / 6°	6755	7055	7355	6455	6755	7055
ZSM470	4700	3250 *3400	3800 *4000	4050 *4200	2495	1274	1692	6° / 6°	6775	7075	7375	6475	6775	7075
ZSM480	4800	3150 *3300	3700 *3900	3950 *4100	2530	1307	1725	6° / 6°	6785	7085	7385	6485	6785	7085
ZSM500	5000	3050 *3200	3400 *3800	3800 *4000	2630	1407	1825	6° / 6°	6805	7105	7405	6505	6805	7105
ZSM540	5400	2750 *3000	3100 *3400	3400 *3600	2755	1532	1950	3° / 6°	6845	7145	7445	6545	6845	7145
ZSM600	6000	2400 *2500	2800 *3000	3100 *3400	2995	1772	2190	3° / 6°	6865	7165	7465	6565	6865	7165

Note: (1)Free lift (without backrest) : +365mm;
(2)* Refers to the rated capacity with front dual tyre.

HELI



H series / HIGH EFFICIENT
ENERGY EFFICIENT

4-5 ton H series

INTERNAL COMBUSTION COUNTERBALANCED
FORKLIFT TRUCK

Standard equipments

Standard fork
Standard carriage
M300 standard mast
Standard overhead guard
Single air cleaner
Standard muffler
Control valve (two throw)
Standard pneumatic tyre
Normal seat
Driver's tool

Optional equipments

Cab
Warning light
Dual air cleaner
Heater
Fan
Fire extinguisher
Protecting net
Dual tyre
Solid tyre
Long fork
Suspension seat
Windshield glass
Rear working light
Wide carriage
Control valve (multi throw)
High vertical exhaust
Spark arrested muffler
Catalyst muffler
Tilting cylinder boot
Steering cylinder boot
Two stage free lift mast
Three stage free lift mast

Optional attachments

Side shifter
Fork positioner
Double side shifter
Single double pallet handler
Hinged forks
Rotator
Push/Pulls
Carpet boom
Load stabilizer
Turnaloads
Crane jib
Glass handler
Fork extension
Paper roll clamp
Bale clamp
Drum clamp
Fork clamp
Block clamp
Multi-purpose clamp



[Click Here](#) to visit our website

Email us : sales@ncfork.com.au

Call us : [0437 804 082](tel:0437804082)



4-5 ton H series
INTERNAL COMBUSTION COUNTERBALANCED
FORKLIFT TRUCK

H series / HIGH EFFICIENT
ENERGY EFFICIENT

HELI
LIFTING THE FUTURE

24 YEARS TOP1 FORKLIFT MANUFACTURER AND SALLER
IN CHINA FOR CONSECUTIVE 24 YEARS